

(12) **United States Patent**
Adams, Jr.

(10) **Patent No.:** **US 11,760,425 B2**
(45) **Date of Patent:** **Sep. 19, 2023**

(54) **HANDY HAUL BOX**
(71) Applicant: **Sidney H Adams, Jr.**, Ellerslie, GA (US)
(72) Inventor: **Sidney H Adams, Jr.**, Ellerslie, GA (US)
(73) Assignee: **Sidney H. Adams, Jr.**, Ellerslie, GA (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/061,879**
(22) Filed: **Oct. 2, 2020**

(65) **Prior Publication Data**
US 2022/0105993 A1 Apr. 7, 2022

(51) **Int. Cl.**
B62D 33/02 (2006.01)
B60R 9/06 (2006.01)
(52) **U.S. Cl.**
CPC **B62D 33/0207** (2013.01); **B60R 9/065** (2013.01)
(58) **Field of Classification Search**
CPC B60R 9/065; B60R 9/055; B65D 19/12; B65D 88/121; B65D 2519/00512; B65D 2519/00532; B65D 7/08; B62D 33/0207
USPC 224/403, 404, 457, 524, 526, 527; 296/37.6; D12/414.1; 220/668, 4.28
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

2,688,420 A * 9/1954 Bishop B65D 7/08 220/668
3,105,617 A * 10/1963 Felldin B65D 77/061 222/181.3

4,212,406 A * 7/1980 Mittelman B65D 88/14 220/1.5
4,625,880 A * 12/1986 Pym B65D 88/528 220/1.5
4,830,211 A * 5/1989 Mekhan
4,830,242 A * 5/1989 Painter B60P 3/32 224/404
5,033,662 A * 7/1991 Godin B60R 9/065 224/521
5,595,305 A * 1/1997 Hart
5,934,725 A * 8/1999 Bowers B60P 3/40 296/26.09
6,024,263 A * 2/2000 Lewis, Sr B60R 9/06 224/502
6,318,781 B1 * 11/2001 Mc Kee B60R 9/00 296/26.09
6,422,627 B1 * 7/2002 Kuhn B60P 3/40 296/26.1
6,467,830 B1 * 10/2002 Cortright B60R 13/06 296/26.04


(Continued)

Primary Examiner — Justin M Larson

(57) **ABSTRACT**

A large haul box for use in a pickup or trailer is disclosed. The large haul box includes a pair of long side wall having a top side, a bottom side, an open end and a back end, a back wall coupled between the back ends of the pair of long side walls, a bottom surface coupled to the back wall along a short end and coupled to the pair of long side walls on their bottom sides, a bottom sheathing coupled to the bottom surface, a long side sheathing coupled to each of the pair of long side walls, a back sheathing coupled to the back wall, and a removable box end having a top side, a bottom side, and a pair of short sides between the top and bottom sides for coupling to the open ends of the pair of long side walls along the pair of short sides and oriented to have the bottom side of the removable box end couple to the open end of the bottom surface.

10 Claims, 3 Drawing Sheets




(56)

References Cited

U.S. PATENT DOCUMENTS

6,536,640	B1 *	3/2003	Gent	B60R 9/00 224/403
6,543,659	B2 *	4/2003	Blair	B60R 9/045 220/9.2
6,712,248	B2 *	3/2004	Mitchell	B60R 9/06 224/498
6,845,895	B2 *	1/2005	Jones	B60R 9/065 224/328
6,860,536	B1 *	3/2005	Schimunek	B60P 1/003 296/26.09
7,004,365	B2 *	2/2006	Ingram	B60R 7/14 220/23.91
D577,328	S *	9/2008	Vrbas	D12/414.1
9,623,808	B2 *	4/2017	Bonenberger	...	B60K 2016/003
9,783,129	B2	10/2017	Roach		
10,793,078	B2 *	10/2020	Schuling	B60R 9/065
11,124,247	B2 *	9/2021	Sosnowich	B60R 9/06
2006/0182580	A1	8/2006	Petersen		
2006/0186157	A1 *	8/2006	Dibble	B60R 9/12 224/405
2009/0032530	A1 *	2/2009	Chu	B65D 88/528 220/4.28
2014/0305977	A1 *	10/2014	Sparks	B60P 1/6427 224/404

* cited by examiner






FIG. 2




FIG. 3

1

HANDY HAUL BOX**TECHNICAL FIELD**

This application relates in general to an article of manufacture providing movable storage, and more specifically, to an article of manufacture providing a larger or small haul box for use in a pickup or trailer.

BACKGROUND

There are trailers available with dump beds, dump trucks, back hoes, and front end loaders which require a person to use a tarp to load and unload. This task can be very tedious, time consuming, and messy. The pile of material remains in the location where you unloaded it until the project is completed and can be very unsightly. The Handy Haul Box, however, sits on your trailer or truck bed and you unload your material with ease by opening the vertical slide gate or single swing hinged gate and loading a wheelbarrow with no problem. Afterward, the material can be stored securely in the Handy Haul Box so that material does not remain in sight on the site.

Many landscaping techs deal with homeowners who do not want a pile of materials in their driveways or in front of their homes, or there may be limited workspace. The Handy Haul Box keeps the job neat and clean, as well as eliminates extra delivery costs. Landscaping companies or lawn technicians would love this convenient tool for flower bed restorations and small projects to complete with ease.

Additionally, whenever a person is laying sod and requires extra dirt or topsoil, they typically purchase the topsoil by the bag or by the truck load. If a person is restoring or creating a flower bed which may require rocks, gravel, or the like, purchasing these items by the bag will be costly and more expensive than having a truck load of material delivered. Requesting these items to be delivered by truck will add cost and time to the project with assurance that there will be no problems with the delivery. Companies are often behind on deliveries and there are additional delivery charges to locations outside the free delivery area.

Therefore, a need exists for an article of manufacture providing a larger haul box for use in a pickup or trailer according to the present invention. The present invention attempts to address the limitations and deficiencies of prior solutions according to the principles and example embodiments disclosed herein.

SUMMARY

In accordance with the present invention, the above and other problems are solved by providing an article of manufacture for a larger haul box for use in a pickup or trailer according to the principles and example embodiments disclosed herein.

In one embodiment, the present invention is an article of manufacture for providing a larger haul box for use in a pickup or trailer. The large haul box includes a pair of long side wall having a top side, a bottom side, an open end and a back end, a back wall coupled between the back ends of the pair of long side walls, a bottom surface coupled to the back wall along a short end and coupled to the pair of long side walls on their bottom sides, a bottom sheathing coupled to the bottom surface, a long side sheathing coupled to each of the pair of long side walls, a back sheathing coupled to the back wall, and a removable box end having a top side, a bottom side, and a pair of short sides between the top and

2

bottom sides for coupling to the open ends of the pair of long side walls along the pair of short sides and oriented to have the bottom side of the removable box end couple to the open end of the bottom surface. Each long side wall comprising a pair of long members and a plurality of short members coupled between the pair of long support members. The back wall comprises a top side support member, a bottom side support member, and a plurality of short members coupled between the top and bottom side support members. The bottom surface comprising a bottom pair of long members and a center long member, each of which is coupled to the bottom side support members of the pair of long side walls. The removable box end comprises a pair of end support members and a plurality of short support members between the pair of end support members.

In another aspect of the present disclosure, the removable box end engages an attachment groove along the open end of the pair of long sides and is secured by a pair of attachment bolts being threaded through the attachment grooves and through the removable box end.

In another aspect of the present disclosure, the removable end further comprises a removable end sheathing coupled to an inner side.

In another aspect of the present disclosure, the bottom sheathing, long side sheathing, back sheathing, and removable end sheathing are made of 16 gauge diamond plated aluminum.

In another aspect of the present disclosure, the long support members, the plurality of short support members, top and bottom side support members, and the end support members being made of 16 gauge 1" by 1" tube steel.

In another aspect of the present disclosure, the top sides of the long side walls further comprise a plurality of side attachment points for securing the article to a truck bed and a trailer.

In another aspect of the present disclosure, the top side support member of the back wall comprises a pair of eyehooks for securing the article to a truck bed and a trailer.

In another aspect of the present disclosure, the long side walls are 8 feet long by 14" high and the back wall is 4 foot long by 14" high.

In another aspect of the present disclosure, the long side walls are 7 feet long by 12" high and the back wall is 3 foot long by 12" high.

In another aspect of the present disclosure, the bottom surface is 8 feet long by 4 feet wide.

The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter that form the subject of the claims of the invention.

It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims. The novel features that are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of

illustration and description only, and is not intended as a definition of the limits of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

FIG. 1 illustrates an example embodiment of an article of manufacture for providing a larger haul box for use in a pickup or trailer according to the present invention.

FIG. 2 illustrates another example embodiment of an article of manufacture for providing a larger haul box for use in a pickup or trailer according to the present invention.

FIG. 3 illustrates an example embodiment of an article of manufacture for providing a removable haul box end for use in a pickup or trailer according to the present invention.

DETAILED DESCRIPTION

This application relates in general to an article of manufacture for providing movable storage, and more specifically, to an article of manufacture for providing a larger haul box for use in a pickup or trailer according to the present invention.

Various embodiments of the present invention will be described in detail with reference to the drawings, wherein like reference numerals represent like parts and assemblies throughout the several views. Reference to various embodiments does not limit the scope of the invention, which is limited only by the scope of the claims attached hereto. Additionally, any examples set forth in this specification are not intended to be limiting and merely set forth some of the many possible embodiments for the claimed invention.

In describing embodiments of the present invention, the following terminology will be used. The singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a needle” includes reference to one or more of such needles and “etching” includes one or more of such steps. As used herein, a plurality of items, structural elements, compositional elements, and/or materials may be presented in a common list for convenience. However, these lists should be construed as though each member of the list is individually identified as a separate and unique member. Thus, no individual member of such list should be construed as a de facto equivalent of any other member of the same list solely based on their presentation in a common group without indications to the contrary. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

It further will be understood that the terms “comprises,” “comprising,” “includes,” and “including” specify the presence of stated features, steps or components, but do not preclude the presence or addition of one or more other features, steps or components. It also should be noted that in some alternative implementations, the functions and acts noted may occur out of the order noted in the figures. For example, two figures shown in succession may in fact be executed substantially concurrently or may sometimes be executed in the reverse order, depending upon the functionality and acts involved.

As used herein, the term “about” means that dimensions, sizes, formulations, parameters, shapes, and other quantities and characteristics are not and need not be exact, but may be approximated and/or larger or smaller, as desired, reflecting tolerances, conversion factors, rounding off, measurement

error and the like, and other factors known to those of skill. Further, unless otherwise stated, the term “about” shall expressly include “exactly.”

The terms “worker,” and “user” refer to an entity, e.g. a human, using the Handy Haul Box associated with the invention. The term user herein refers to one or more users.

The term “invention” or “present invention” refers to the invention being applied for via the patent application with the title “Handy Haul Box.” Invention may be used interchangeably with box.

In general, the present disclosure relates to an article of manufacture for providing movable storage. To better understand the present invention, FIG. 1 illustrates an example embodiment of an article of manufacture providing a larger haul box for use in a pickup or trailer according to the present invention.

The Handy Haul Box **100** is made of light gauge metal material which has been welded together and light gauge diamond plated aluminum siding to enclose the framing with a double gate access for unloading along with four anchor points. The Handy Haul Box **100** is 14" tall by 4'0" wide by 8'0" long, as shown in FIGS. 1-2, also available in a smaller size-12" tall by 3'0" wide by 7'0" long (not shown) which will accommodate any pickup truck bed or trailer.

The Handy Haul Box **100** has a multi-purpose use for assisting in transporting rocks, sand, dirt, or even sensitive items. This item will primarily be used by homeowners, landscaping companies, and lawn services that utilize a pick-up truck or trailer to pick up a ½ to 1 yard of rock, sand, dirt, etc. Use of the Handy Haul Box **100** will eliminate the delivery fees and save time.

The first embodiment was made of untreated wood with 2'x4' and ¾" plywood. After some experimental use, the first embodiment was determined to be too heavy for one person to load onto a trailer. After 6 loads of 1 yard of river rocks (about 2600 lbs.), stress on the walls of the box **100** began to show, and anchoring and securing the box **100** to the trailer was also putting stress on the box.

The second embodiment is made of 16 gauge 1"x1" tube steel. This box **100** is lighter and more rigid. The box **100** will not have the stress damage of the first embodiment and will keep its integrity even when anchored down with industrial rigging equipment. The second embodiment may be loaded onto a pickup or trailer by one person.

The Third embodiment is made of welded light gauge material and light gauge aluminum siding (plywood sheathing was removed after observing that the weather elements will shorten the life of the material). The light gauge Diamond Plated Aluminum base and siding solidifies the Handy Haul Box will help the longevity and endure the harsh weather conditions. Also, the side supports were added to fortify the side walls to the base of the frame which will overall makes the Handy Haul Box more rigid.

The Handy Haul Box **100** may be constructed with a box frame **101** and a removable box end **102**. Both of these items may be coupled to solid side material, for example plywood to create an enclosed box capable of holding yard material. Other material, such as steel or aluminum, also may be used as long as the material is strong enough to support the weight of the yard material hauled in the box.

The box frame **101** comprises a plurality of long support members **111a-e** that are used for the top and bottom supports of the Handy Haul Box **100**. On each side of the box **100** a pair of long support members **111a-b** and **111c-d** are connected by a plurality of short support members **121a-d** and **121f-i** to define the two long side walls **103a-b** of the box **100**. These two sides are covered by siding

5

material **132a-b**. The aluminum siding has side wall supports which is made from 1/8" thick 1" by 1" metal angle. These supports reinforce and strengthens the walls by adjoining the aluminum siding material to the main frame or the base.

A back wall **104** may be constructed using a pair of side support members **112a-b** connected by a set of additional short support members **121d-121f**. Each of the two ends of the back wall **104** are coupled to one of two ends of the pair of long side walls **103a-b** of the box **100**. The back wall **104** also may be covered by siding material **133b**.

One additional long support member **111e** is connected to the center of the bottom short support member **112b** and oriented to run parallel to the two long side walls **103a-b**. A set of base support members **122a-d** connect the additional long support member **111e** to the two bottom support members **111b**, **111d** of the two long side walls **103a-b** to form a base or bottom of the box **100**. Siding material **131** covers these base support members forming an enclosed box **100** with the two long side walls **103a-b** and the back wall **104**. A removable box end **102** attaches to an open end of the box where the removable box end **102** couples to the ends of the long side walls **103a-b**. A set of base support rails **131a-c** are shown along a bottom outer edge of the box **100** at the bottom of the second side wall **103b**. An identical set of support rails (not shown) are located along a bottom outer edge of the box **100** at the bottom of the first side wall **103a**.

All of the above support members may be coupled together by welding the ends together in the arrangement shown in FIG. 1 for a preferred embodiment for a box **100** made of tube steel. Other embodiments may connect the support members using mechanical attachment devices such as nuts and bolts, screws, and related hardware components. For an embodiment in which the support members are made of wood, nails may be used.

In order to maintain and keep up the Handy Haul Box **100**, users may clean the Handy Haul Box outside on a moderate day, use a mild soap and water to wash and remove any mud and grease, spray or rinse off with a hose, mix one-part acid to one-part water, such as a cup of vinegar to a cup of water, or use cream of tartar or lemon juice, and use for cleaning. Alternatively, a user may use a metal-polish paste to scrub the furniture in place of the mild acid solution. The Handy Haul Box **100** is scrubbed with the above solution. A gentle dish scrubber may be useful for the cleaning process, to prevent to damage the metal with scratches. Users are trying to remove the discoloration due to oxidation.

The Handy Haul Box **101** may be used with one of more accessories, such as sectional dividers, tarps, hard covers, skid resistance Matting, team logos, and rigging (not shown). Additionally, Forklift Skids may also be mounted onto the Handy Haul Box **101** as needed. Other useful items that may be used with the Handy Haul Box **101** include shackles, chain come alongs, I-bolts, leveling hoists, punching straps, and ratcheting straps among other similar items.

Oxidation is why aluminum doesn't rust. Though oxidation is a form of corrosion, it forms aluminum oxide, which creates a hard, protective barrier that shields the metal from water. However, it does build up over time, and the discoloration lessens the beauty of the Handy Haul Box. Once complete, Rinse off the solution with a hose.

FIG. 2 illustrates another example embodiment of an article of manufacture for providing a larger haul box for use in a pickup or trailer according to the present invention. The Handy Haul Box **100** is shown having a pair of eye hook attachments **201a-b** along the top edge of the back wall **104**. These eye hooks may be used to tie down the box to a trailer

6

or pickup bed when hauling items to a job site. A plurality of side attachment points **202a-d** are located along the top edge of the pair of long side walls **103a-b** to assist in restraining the box when on a trailer or pickup bed. In a preferred embodiment, the side attachment points **202a-d** are positioned above a short support member used **121b-c** and **121g-h** to create the long side walls **103a-b**.

The removable box end **102** attaches to the open end of the box **100** by sliding into a pair of attachment grooves **203a-b** attached to the sides of the long side walls **103a-b** at the open end of the box **100**. The removable box end **102** slides downward into the attachment grooves **203a-b** with a pair of shorter ends of the removable box end **102** fitting within the grooves **203a-b**. A pair of attachment bolts **301a-b** couple the sides of the removable box end **102** to the open end of the box **100** as the attachment bolts are threaded through holes in the sidewalls of the attachment grooves **203a-b** after pass through the removable box end **102**.

There are six anchor points on the Handy Haul Box that can be used to secure the box while being transported. I-bolts bores are provided on the frame **112a**, **111c** and **111a**. The holes at **201a, 201b**, **202b**, **202a**, **202c** and **202d** are provided for I-bolt rigging (recommended with shackle use). Also, leveler hoists, ratchet straps, chain come-along, proper roping and tow chains can be used to secure the Handy Haul Box to the truck bed or trailer. A skid resistant felt can be placed under the Handy Haul Box in line with proper rigging to ensure zero movement of box while transporting a load.

FIG. 3 illustrates an example embodiment of an article of manufacture providing a removable haul box end for use in a pickup or trailer according to the present invention. The removable box end **102** comprises a pair of side support members **311a-b** that are connected together with opposing ends of a plurality of short support members **312a-d** coupled to the sides of the side support members **311a-b**. A pair of handles **302a-b** are coupled along the top edge of the removable box end **102** for lifting the removable box end **102** out of the attachment grooves **203a-b** along the open end of the box **100**. As shown in FIG. 1, siding material **133a** may be attached to the sides of the removable box end **102** to complete the enclosure of the box **100** when installed into the attachment grooves **203a-b**. The pair of attachment bolts **301a-b** may be located through the short support members **312a**, **312d** that define the outer edge of the removable box end **102**.

Even though particular combinations of features are recited in the present application, these combinations are not intended to limit the disclosure of the invention. In fact, many of these features may be combined in ways not specifically recited in this application. In other words, any of the features mentioned in this application may be included to this new invention in any combination or combinations to allow the functionality required for the desired operations.

No element, act, or instruction used in the present application should be construed as critical or essential to the invention unless explicitly described as such. Further, the phrase "based on" is intended to mean "based, at least in part, on" unless explicitly stated otherwise.

What is claimed is:

1. An article of manufacture for providing a haul box for use in a pickup or trailer, the haul box comprises:
 - a pair of long side walls having a top side, a bottom side, an open end and a back end, each long side wall comprising a pair of long members and a plurality of short members coupled between the pair of long support members;

7

- a back wall coupled between the back ends of the pair of long side walls, the back wall comprises a top side support member, a bottom side support member, and a plurality of short members coupled between the top and bottom side support members;
- a bottom surface coupled to the back wall along a short end and coupled to the pair of long side walls on their bottom sides, the bottom surface comprising a pair of base support members, each of which is coupled to the long members of the pair of long side walls, and a center long member;
- a bottom sheathing coupled to the bottom surface;
- a long side sheathing coupled to each of the pair of long side walls;
- a back sheathing coupled to the back wall; and
- a removable box end having a top side, a bottom side, and a pair of short sides between the top and bottom sides for coupling to the open ends of the pair of long side walls along the pair of short sides and oriented to have the bottom side of the removable box end couple to an open end of the bottom surface, the removable box end comprises a pair of end support members and a plurality of short support members between the pair of end support members.
2. The haul box according to claim 1, wherein the removable box end engages an attachment groove along each open end of the pair of long sides and is secured by a

8

pair of attachment bolts being threaded through the attachment grooves and through the removable box end.

3. The haul box according to claim 2, wherein the removable end further comprises a removable end sheathing coupled to an inner side.

4. The haul box to claim 3, wherein the bottom sheathing, long side sheathing, back sheathing, and removable end sheathing are made of $\frac{1}{8}$ " thick 1" by 1" metal angle.

5. The haul box according to claim 3, wherein the long members, the plurality of short members, top and bottom side members, and the end members being made of 16 gauge 1" by 1" tube steel.

6. The haul box according to claim 5, wherein the top sides of the long side walls further comprise a plurality of side attachment points for securing the article to a truck bed and a trailer.

7. The haul box according to claim 5, wherein the top side support member of the back wall comprises a pair of eyehooks for securing the article to a truck bed and a trailer.

8. The haul box according to claim 1, wherein the long side walls are 8 feet long by 14" high and the back wall is 4 foot long by 14" high.

9. The haul box according to claim 1, wherein the long side walls are 7 feet long by 12" high and the back wall is 3 foot long by 12" high.

10. The haul box according to claim 8, wherein the bottom surface is 8 feet long by 4 feet wide.

* * * * *