

(12) **United States Patent**
Puchosic et al.

(10) **Patent No.:** **US 10,907,945 B2**
(45) **Date of Patent:** **Feb. 2, 2021**

(54) **BULLET LOADER**

(56) **References Cited**

(71) Applicants: **Gary Lee Puchosic**, Orange Park, FL (US); **Michael Wallale Hansen**, Jacksonville, FL (US)

(72) Inventors: **Gary Lee Puchosic**, Orange Park, FL (US); **Michael Wallale Hansen**, Jacksonville, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/734,365**

(22) Filed: **Jan. 5, 2020**

(65) **Prior Publication Data**
US 2020/0393227 A1 Dec. 17, 2020

U.S. PATENT DOCUMENTS

1,739,996 A * 12/1929 White A43D 100/08
221/243
2,371,126 A * 3/1945 Best et al. B65G 47/1457
86/54
3,430,808 A * 3/1969 Matthews G05D 9/12
221/10
3,628,273 A * 12/1971 Lach F42B 33/002
42/87
3,659,492 A * 5/1972 Fullmer B65G 47/1457
86/46
4,312,438 A * 1/1982 Vatsvog F42B 33/002
198/392
5,335,578 A * 8/1994 Lorden F42B 33/002
86/25
7,497,155 B2 * 3/2009 Koskela F42B 33/10
86/23
7,552,668 B1 * 6/2009 Gonzalez F42B 33/00
86/45
7,665,490 B1 * 2/2010 Elliott B29O 48/285
141/284
8,096,403 B2 * 1/2012 Marti Sala B65G 47/256
198/384

(Continued)

Primary Examiner — Joshua E Freeman

Related U.S. Application Data

(60) Provisional application No. 62/788,791, filed on Jan. 5, 2019.

(51) **Int. Cl.**
F42B 33/00 (2006.01)
B65G 47/248 (2006.01)


(52) **U.S. Cl.**
CPC **F42B 33/002** (2013.01); **B65G 47/248** (2013.01)

(58) **Field of Classification Search**
CPC F42B 33/002; F42B 33/00; B65G 47/248
USPC 86/45, 23, 46, 43, 24
See application file for complete search history.

(57) **ABSTRACT**

An improved bullet loader system applies bullets to a feed tube from a source of bullets. The bullets each have a tip-end and a base-end. The bullet-orienting system includes a bullet conveyance that conveys bullets, in tip-end-down and tip-end-up orientations, from a source of bullets to a feed tube along a bullet conveyance path. A bullet-orienting structure comprising a block, a nose guide forming a ledge, a groove, and a tapered opening, and a ramp is disposed at a fixed location proximate the bullet conveyance path. For each tip-end-down oriented bullet, the bullet-orienting structure interacts with the tip-end-down bullet, and flips the tip-end down bullet relative to the bullet conveyance from tip-end-down orientation to the tip-end-up orientation prior to application to the feed tube.

10 Claims, 15 Drawing Sheets




(56)

References Cited

U.S. PATENT DOCUMENTS


8,661,959	B2 *	3/2014	Koskela	F42B 33/002	86/45
9,879,960	B2 *	1/2018	Bergmann	F42B 33/002	
9,989,342	B1 *	6/2018	Lougeay	F42B 33/002	
10,718,599	B1 *	7/2020	Kirsch	F42B 33/001	
2002/0121184	A1 *	9/2002	Fowler	F42B 33/002	86/45
2004/0025678	A1 *	2/2004	Shields	F42B 33/02	86/31
2008/0053297	A1 *	3/2008	Koskela	F42B 33/10	86/27
2013/0125737	A1 *	5/2013	Koskela	B65G 47/1457	86/45
2013/0152771	A1 *	6/2013	Coma Asensio	F42B 33/00	86/19.5
2016/0305726	A1 *	10/2016	Mokuolu	F41A 9/83	
2016/0313103	A1 *	10/2016	Bergmann	F42B 33/002	

* cited by examiner



PRIOR ART

FIG. 1



PRIOR ART

FIG. 2




FIG. 3a




FIG. 3b




FIG. 3c




FIG. 4a




FIG. 4b




FIG. 4c




FIG. 4d




FIG. 4e




FIG. 5a




FIG. 5b




FIG. 6a




FIG. 6b




FIG. 7a




FIG. 7b




FIG. 7c




FIG. 7d




FIG. 7e




FIG. 7f

1

BULLET LOADER

The instant application claims the benefit of the prior filing of U.S. Provisional Application to Puchosic et al, Ser. No. 62/788,791, filed Jan. 5, 2019. This provisional application is incorporated by reference as if it was recited herein in its entirety.

TECHNICAL FIELD

This application relates in general to an improvement to a bullet loader, and more specifically to improvements to existing automated bullet loaders utilizing a rotating wheel to properly orient various bullet caliber sizes being used in loading and reloading casings.

BACKGROUND

Ammunition consists of the projectiles and propelling charges used in small arms, artillery, and other guns. Ammunition size is usually expressed in terms of caliber, which is the diameter of the projectile as measured in millimeters or inches. In general, projectiles less than 20 mm or 0.60 inch in diameter are classified as small-arm, and larger calibers are considered artillery. A complete round of ammunition, which is referred to as a fixed type round, consists of all the components necessary for one firing of the gun. These normally included a projectile, the propellant, and a primer that ignites the propellant. Other components such as the cartridge case, fuse, bursting charge, and lubricant are frequently included.

Modern small-arms ammunition is nearly always of the fixed type. Complete rounds are usually called cartridges, and projectiles are called bullets. Cartridge cases or shells are most commonly made of brass, although steel is also widely used. Many varieties of bullets are cast from lead and can have lubricant or grease grooves formed on the bullet outer surface.

Handloading is the process used to create firearm cartridges by hand versus those put together en masse and sold commercially, generally in packages of 6 to 50. When previously-fired cases or shells are used, the process is often called reloading. Specific details of handloading and reloading can be found in U.S. Pat. Nos. 8,661,959, 7,497,155 and 7,549,364, issued to Richard Koskela, the disclosures of which are incorporated herein by reference.

After casting bullets from lead, it can be desirable to apply lubricant to any lubricant or grease grooves formed on the bullets' outer surfaces. Lubricant is applied to the bullet so that when a bullet is fired, the lubricant is transferred along the passage of the bullet down a rifled bore. Generally, lubricant is transferred from the bullet grease groove to the bore surface through compression, linear acceleration, and radial acceleration when the bullet is fired. Additionally, lubricant is injected forward during the firing process due to high-pressure gas leakage into the lubrication groove.

Some methods and apparatuses useful for applying lubricant require a bullet to be oriented with its tip-end facing down. Additionally, other bullet or projectile systems also may require a tip-end-down oriented bullet. Acceptable means for dispensing tip-end-down oriented bullets are not found in the prior art. The prior art includes inefficient devices that simply reject improperly oriented bullets rather than reorient them and devices that are simply too large or expensive for smaller applications. Unfortunately, while skilled artisans have devoted considerable effort toward the development and improvement of bullet-orienting systems,

2

current efforts have not yielded entirely acceptable results, without need for complex configuration of bullet loader apparatus for each bullet caliber sizes. Given the deficiencies prevalent in the art, the need for continued improvement is evident.

The present invention attempts to address the existing limitations in bullet loaders when configured for various caliber sized bullets according to the principles and example embodiments disclosed herein.

SUMMARY

In accordance with the present invention, the above and other problems are solved by providing an apparatus for improved operation as a configurable bullet loader.

In one embodiment, the present invention is an apparatus bullet-orienting apparatus for orienting bullets comprising a tip-end and a base-end. The apparatus having a bullet conveyance comprising a wheel having a perimeter defining one or more notches wherein each notch is sized to accommodate a bullet resting with either its tip-end or its base-end facing a nose plate when the notch is positioned above the nose plate, and a bullet-orienting structure positioned adjacent the bullet conveyance such that a bullet conveyed from an upstream location to a downstream location by the bullet conveyance interacts with the bullet-orienting structure. The bullet-orienting structure includes the nose plate that extends at least partially below the wheel and being movable relative to the wheel, wherein the nose plate defines a tapered opening and a groove having a first end and a second end, wherein the first end of the groove is disposed adjacent to the tapered opening and wherein the tapered opening is positioned such that it is partially extends beneath the perimeter of the wheel and such that a bullet positioned in a notch of the wheel and oriented with its tip-end facing toward the tapered opening would fall into the tapered opening and such that a bullet positioned in a notch of the wheel and oriented with its base-end facing toward the tapered opening would not fall into the tapered opening, a spacer adjacent to the nose plate below the wheel to orient the nose plate such that the groove is located in a position corresponding to a bullet caliber size to be processed, and a fixed location ramp having a first end and a second end, wherein the first end of the ramp is disposed adjacent to the second end of the groove, wherein the ramp is positioned downstream from the tapered opening, and wherein a bullet positioned in a notch with its base-end facing toward the tapered opening would interact with the ramp. The fixed location ramp comprises either a pistol bullet ramp and a rifle bullet ramp.

In a second embodiment, the present invention is an apparatus including a bullet conveyance conveying bullets along a bullet conveyance path from an upstream location to a bullet-receiving opening at a downstream location, the bullets each including a tip end having a first width and a base end having a second width greater than the first width, the bullet conveyance taking up the bullets in tip down and tip up orientations whereby each of the bullets taken up by the bullet conveyance in the tip up orientation comprises a tip up bullet and each of the bullets taken up by the bullet conveyance in the tip down orientation comprises a tip down bullet; and bullet-orienting structure interacting with each tip down bullet conveyed along the bullet conveyance path by the bullet conveyance between the upstream location and the downstream location rotating each tip down bullet relative to the bullet conveyance from the tip down orientation to the tip up orientation. The bullet-orienting structure includes: a nose plate that extends at least partially below the

wheel and being movable relative to the wheel, wherein the nose plate defines a tapered opening and a groove having a first end and a second end, wherein the first end of the groove is disposed adjacent to the tapered opening and wherein the tapered opening is positioned such that it is partially extends beneath the perimeter of the wheel and such that a bullet positioned in a notch of the wheel and oriented with its tip-end facing toward the tapered opening would fall into the tapered opening and such that a bullet positioned in a notch of the wheel and oriented with its base-end facing toward the tapered opening would not fall into the tapered opening, a spacer adjacent to the nose plate below the wheel to orient the nose plate such that the groove is located in a position corresponding to a bullet caliber size to be processed, a rotating knob having a thru screw to attach the nose plate into a desired location after the spacer has been installed, a groove receiving the tip of each tip down bullet initially rotating each tip down bullet out of the tip down orientation toward the tip up orientation; and a fixed location ramp receiving the tip of each tip down bullet initially rotated from the groove rotating each tip down bullet into the tip up orientation; The fixed location ramp comprises a pistol bullet ramp and a rifle bullet ramp. The rifle bullet ramp includes: a longer outside ramp having a first front edge and a rising slope to a first back edge and a shorter inside ramp having a second front edge and a rising slope to a second back edge, the second back edge being adjacent to an intersection point along a front side of the longer outside ramp, and a front side of the shorter inside ramp oriented from the front side of the longer outside ramp at an angle of 45° measured between the first front edge and the second front edge. The pistol bullet ramp comprises a solid ramp having the following approximate dimensions: an outside height of 36.50 mm, an inside length of 42.45 mm, an outside edge radius length of 53.50 mm, an inside edge radius length of 42.45 mm, a front length of 22.80 mm, a back length of 26.00 mm, a lower edge length of 23.04 mm, and a front ledge height of 2.0 mm. The spacer comprises a solid item having a width corresponding to the bullet caliber size being processed. The wheel comprises a flat rotating disk and a handle coupled to a top side of the disk perpendicular to the top side of the disk.

The great utility of the invention is that that configuration of the apparatus for processing of various caliber sized bullets is simplified.

The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter that form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims. The novel features that are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

FIG. 1 represents a prior art representation of a prior art bullet loader improved by use of the present invention.

FIG. 2 illustrates a prior art representation of a wheel used within a bullet loader improved by the present invention.

FIG. 3a-c illustrates various embodiments of a bullet orientation ramp according to the present invention.

FIG. 4a-e illustrates various embodiments of a bullet orientation block utilizing varying sized spacers according to the present invention.

FIG. 5a-b illustrates various embodiments of a bullet path support according to the present invention.

FIG. 6a-b illustrates various embodiments of a wheel removal handle according to the present invention.

FIG. 7a-7f illustrates various embodiments of a bullet loader orientation jigs according to the present invention.

DETAILED DESCRIPTION

This application relates in general to a method and article of manufacture for providing an apparatus for providing a bullet loader.

Various embodiments of the present invention will be described in detail with reference to the drawings, wherein like reference numerals represent like parts and assemblies throughout the several views. Reference to various embodiments does not limit the scope of the invention, which is limited only by the scope of the claims attached hereto. Additionally, any examples set forth in this specification are not intended to be limiting and merely set forth some of the many possible embodiments for the claimed invention.

As used herein, the singular forms "a," "an," and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It further will be understood that the terms "comprises," "comprising," "includes," and "including" specify the presence of stated features, steps, or components but do not preclude the presence or addition of one or more other features, steps, or components. It also should be noted that in some alternative implementations, the functions and acts noted may occur out of the order noted in the figures. For example, two figures shown in succession may in fact be executed substantially concurrently or may sometimes be executed in the reverse order, depending upon the functionality and acts involved.

In general, the present disclosure relates to an apparatus for providing a bullet loader. More specifically to improvements to existing automated bullet loaders utilizing a rotating wheel to properly orient various bullet caliber sizes being used in loading and reloading casings.

To better understand the present invention, FIG. 1 represents a prior art representation of a prior art bullet loader improved by use of the present invention. The bullet loader **101** shown here is a Mr. BULLETFEEDER® automated bullet loader manufactured and sold by Double Alpha Academy of Orefield, PA and RAK Systems, LLC of Scottsdale, Ariz. The design and operation of the automated bullet loader **101** is described in detail in the previously referenced U.S. Pat. Nos. 8,661,959, 7,549,364, and 7,497,155, all to Koskela. FIG. 1 illustrates the entire automated bullet loader **101** as configured to load various caliber sized bullets into casings.

FIG. 2 illustrates a prior art representation of a wheel used within a bullet loader improved by the present invention. The wheel **201** rotates in the direction of A with bullets

5

falling into the spaces around the diameter of the wheel. As wheel **201** rotates, the bullets orientation gap **202** and bullet orientation ramp **203** which will ensure the orientation of the bullet as being tip upward as described in the above patents to Koskela.

FIG. **3a-c** illustrates various embodiments of a bullet orientation ramp according to the present invention. FIG. **3a** illustrates a fixed bullet orientation ramp **301** useful for pistol bullets. The fixed bullet orientation ramp **301** is attached to a base element supporting the rotating wheel **201** within the bullet loader **101**. In prior art systems, the fixed bullet orientation ramp **301** requires adjustment of its placement relative to the wheel **201** depending upon a caliber size bullet being processed at a given point in time. Different wheels **201** are used when a differing caliber bullet size is to be processed. When switching bullet caliber sizes, the wheel **201** corresponding to that particular caliber size is used.

When a wheel is changed, prior art fixed bullet orientation ramp **301** requires it to be configured to operate at a different distance from the wheel depending upon the length of the bullet caliber size. Such configuration may present difficulty in use and possible lead to operating errors. Use of the improved fixed bullet orientation ramp **301** disclosed herein

6

permits the operation of bullet loader **101** with any caliber sized bullet and corresponding wheel **201** without replacement and configuration.

The improved fixed bullet orientation ramp **301** is shown in FIG. **3a** and possesses the following dimensions in a preferred embodiment:

Outside height 302	36.50 mm;
Inside length 303	42.45 mm;
Outside edge radius length 304	53.50 mm;
Inside edge radius length 305	42.45 mm;
Front Length 306	22.80 mm;
Back Length 307	26.00 mm;
Lower edge length 308	23.04 mm; and
Front ledge height 309	2.0 mm.

Table 1 illustrates the pistol bullet caliber of example manufacturers relationship to the bullet orientation ramp and related components as described herein. Within Table 1, the ramp indications for Mr. Bullet refer to a ramp originally designed and included in a bullet loader as described in the patents to Koskela. References to Pistol for this ramp indications refer to the improved fixed bullet orientation ramp **301** described above.

TABLE 1

PISTOL PROFILE CHART & 7 Bullet Spacers						
CALIBER	BULLET WEIGHT	BULLET PROFILE	MANUFACTURER	SPACER	RAMP	SHIMS
380	95 Grain	RN	Montana Gold	4	Mr. Bullet	All
ACP	95 Grain	RN	Bayou Bullet	4	Mr. Bullet	All
	105 Grain	FP	Bayou Bullet	4	Pistol	All
9 mm	115 Grain	RN	Berry's FMJ	5	Pistol	None
	115 Grain	RN	Bayou Bullet	5	Pistol	None
	115 Grain	CONE	Eggelston	5	Pistol	None
	120 Grain	FP	Bayou Bullet	5	Pistol	None
	124 Grain	CONE	Eggelston	5	Pistol	None
	125 Grain	CONE	Any	5	Pistol	None
	147 Grain	FP	Bayou Bullet	5	Pistol	None
	147 Grain	RN	Eggelston	5	Pistol	None
	147 Grain	RN	Berry's FMJ	5	Pistol	None
	147 Grain	FP	Berry's FMJ	4	Pistol	None
38 SPL	125 Grain	XTP HP	Hornady	4	Pistol	None
357	140 Grain	XTP HP	Hornady	4	Pistol	None
MAG	145 Grain	SILVERTIP HP	Winchester	4	Pistol	None
	158 Grain	XTP HP	Hornady	4	Pistol	None
	158 Grain	SWC	Bayou Bullet	5	Pistol	None
	160 Grain	RN	Bayou Bullet	5	Pistol	None
357 SIG	See 9 mm bullets					
40 S&W	155 Grain	RN	Bayou Bullet	2	Pistol	None
10 mm	165 Grain	FP	Eggelston	2	Pistol	None
	165 Grain	FP	Berry's FMJ	2	Pistol	None
	180 Grain	RN	Magma Mold	2	Pistol	None
	180 Grain	FP	Bayou Bullet	2	Pistol	None
	180 Grain	FP	Eggelston	2	Pistol	None
	180 Grain	FPRS	Berry's Plated	2	Pistol	None
	180 Grain	JHP	Montana Gold	2	Pistol	None
	180 Grain	RNFP	Winchester	2	Pistol	None
	180 Grain	XTP HP	Hornady	2	Pistol	None
	200 Grain	RN	Bayou Bullet	2	Pistol	None
41 MAG	210 Grain	SWC	Bayou Bullet	1	Pistol	2 thick shims
	215 Grain	SWC	Bayou Bullet	1	Pistol	2 thick shims
	220 Grain	SWC	SP Speer	1	Pistol	1 thick shim
44 SPL	200 Grain	RNFP	Eggelston	1	Pistol	2 thick shims
44	215 Grain	SWC	Bayou Bullet	1	Pistol	2 thick shims
MAG	240 Grain	SWC	Bayou Bullet	1	Pistol	1 thick shim
	245 Grain	SWC	Lee Cast Bullet	1	Pistol	1 thick shim
45 LC	200 Grain	RNFP	Bayou Bullet	1	Pistol	2 thick shims
	250 Grain	RNFP	Bayou Bullet	1	Pistol	2 thick shims
	255 Grain	SWC	Lee Cast Bullet	1	Pistol	2 thick shims
45 ACP	200 Grain	FP	Berry's FMJ	1	Pistol	None
45 GAP	200 Grain	SWC	Eggelston	2	Pistol	None
	200 Grain	RN	Bayou Bullet	2	Pistol	None
	230 Grain	RN	Berry's FMJ	2	Pistol	None

TABLE 1-continued

PISTOL PROFILE CHART & 7 Bullet Spacers						
CALI-BER	BULLET WEIGHT	BULLET PROFILE	MANU-FACTURER	SPACER	RAMP	SHIMS
	230 Grain	RN	Eggelston	2	Pistol	None
	230 Grain	RN	Bayou Bullet	2	Pistol	None
	230 Grain	SWC	Berry's FMJ	2	Pistol	None
	230 Grain	FPHB	Berry's FMJ	1	Pistol	None
	230 Grain	RN	Frontier FMJ	2	Pistol	None
	230 Grain	RN	Frontier CMJ	2	Pistol	None
	230 Grain	XTP HP	Hornady	1	Pistol	None

Pistol notes:

CONE - Conical shape

CMJ - Complete Metal Jacket

FP - Flat Point *

FPHB - Flat Point Hollow Base

FPRS - Flat Point Round Shoulder *

HP -Hollow Point

HPBT - Hollow Point Boat Tail

FMJ - Full Metal Jacket

*FP & FPRS - can also be referred to as TC - Truncated Cone

JHP - Jacketed Hollow Point

RN - Round Nose

RNEP - Round Nose Flat Point

SP - Soft Point

SWC - Semi Wad Cutter

XTP HP - Hornady Hollow Point

Table 2 illustrates the rifle bullet caliber of example manufacturers relationship to the bullet orientation ramp of FIG. 3b and related components as described herein.

TABLE 2

RIFLE PROFILE CHART				
BULLET	PLATE	SPACER	SHIMS	RAMP
30 Cal Bullets				
308, 300 blackout, 300win mag, 30/30, 30 cal Bullets (size .308/.309)				
Sierra Varminter 110 gr HP	308 Half Plate	5A	None	Rifle
Hornady V Max 110 gr	308 Half Plate	5A	None	Rifle
Hornady 110 gr FMJ	308 Half Plate	5A	None	Rifle
Speer 125 gr FMJ HP	308 Full Plate	5A	None	Rifle
Hornady V Max 150 gr FMJ	308 Full Plate	5A	None	Rifle
163 gr FMJ AP	308 Full Plate	5A	None	Rifle
Sierra Game King 165 gr HPBT	308 Full Plate	5A	None	Rifle
Lyman CnC Bullet 168 gr FP	308 Full Plate	5A	None	Rifle
Nosler 170 gr BTFP	308 Full Plate	5A	None	Rifle
Sierra 170 gr FN	308 Full Plate	5A	None	Rifle
Speer 175 gr soft point	308 Full Plate	5A	None	Rifle
Barnes TTSX 180 gr Ballistic tip	308 Full Plate	5A	None	Rifle
Hornady 208 gr FMJ BTHP	308 Full Plate	5A	None	Rifle
Berrys 220 gr FMJ Spire Point	308 Full Plate	5A	None	Rifle
Lee CnC 230 gr Spire Point	308 Full Plate	5A	None	Rifle
Missouri Bullet 245 gr CnC FP	308 Full Plate	5A	None	Rifle
* The 308 bullet feeder plate splits in half due to the length of certain 30 cal bullets				
7 mm (size .284)				
Hornady 120 gr Spire Point	308 Full Plate	5A	None	Rifle
Hornady 139 gr SST	308 Full Plate	5A	None	Rifle
Sierra Match King 175 gr HPBT	308 Full Plate	6	None	Rifle
Sierra Match King 150 gr HPBT	308 Full Plate	6	None	Rifle
** 7 mm bullets should be run no faster than half speed for reliability				
303 British (size .311)				
Sierra Match King 174 gr HPBT	308 Full Plate	6	None	Rifle
AK 47 (size .311 or .312)				
Berrys 123 gr Spire point	308 Half Plate	6	All Shims	Rifle

TABLE 2-continued

RIFLE PROFILE CHART				
BULLET	PLATE	SPACER	SHIMS	RAMP
<u>270 and 6.8 (size .277)</u>				
Remington 130 gr spritzer SP	308 Full Plate	5A	None	Rifle
Nosler 150 gr BT Ballistic tip	308 Full Plate	6	None	Rifle
Hornady 130 gr spire point	308 Full Plate	6	None	Rifle
Nosler 130 gr Ballistic Tip Spitzer	308 Full Plate	6	None	Rifle
Hornady 110 gr BTHP	308 Full Plate	6	None	Rifle
Nosler 115 gr BTHP	308 Half Plate	6	None	Rifle
<u>243 and 6 mm (size .243/.244)</u>				
Nosler 90 gr Ballistic Tip Spitzer	308 Full Plate	6	None	Rifle
Nosler 130 gr Ballistic Tip Spitzer	308 Full Plate	6	None	Rifle
Nosler 100 gr Ballistic tip Spitzer	308 Full Plate	6	None	Rifle
<u>25 caliber (size .257)</u>				
Nosler 100 gr Ballistic tip Spitzer	308 Half Plate	5A	None	Rifle
<u>6.5 MM (size .264)</u>				
Hornady 120 gr ELD Match (Grendel)	308 Full Plate	5A	1 Shim	Rifle
Hornady 147 gr ELD Match (creedmoor)	308 Full Plate	5A	None	Rifle
<u>223/556 (size .224)</u>				
Hornady 40 gr V Max	223 Plate	6	All Shims	Rifle
Hornady 50 gr V Max	223 Plate	6	All Shims	Rifle
Hornady 55 gr FMJ	223 Plate	6	All Shims	Pistol
Hornady 62 gr FMJ	223 Plate	6	All Shims	Pistol
Hornady 75 gr BTHP Match	223 Plate	6	None	Rifle
Hornady 75 gr V Max	223 Plate	7	None	Pistol
Sierra 55 gr Spitzer	223 Plate	6	All Shims	Pistol
Sierra 55 gr SP	223 Plate	6	All Shims	Pistol
Sierra 77 gr Match King BTHP	223 Plate	7	None	Rifle
*** Works best when running half speed & adjusting hopper angle				
<u>20 Cal (size .204)</u>				
Hornady 32 gr V Max	223 Plate	6	All Shims	Rifle
Hornady 40 gr V Max	223 Plate	6	All Shims	Rifle

Rifle Notes:

The 223/556 bullets will work with either pistol or rifle ramps, however for longer bullets the rifle ramp works better at faster speeds and the angle of the hopper plays more of a critical role and may need to be increased or decreased depending on the bullet length and speed of the hopper. The Barnes TTSX 180 grain 30 Caliber bullet requires less of an angle for more reliable orientation of the bullet as an example of this, and it applies to all calibers.

AP - Armour Piercing

BT - Boat Tail

CNC - Cast & Coated*

* Cast & Coated means a lead bullet with a polymer coating

FIG. 3*b* illustrates and fixed rifle bullet orientation ramp 311 for use with longer rifle caliber bullets. The fixed rifle bullet orientation ramp 311 consist of a smaller ramp 312 having a lower base closest to the wheel 201 and a larger ramp 313 having a middle point 314 adjacent to a longer end of smaller ramp 312. A cap 315 covers a nut that used to attach the fixed rifle ramp 311 to the bullet loader 101. The use of these smaller ramp 312 and larger ramp 314 are oriented to cause a longer rifle bullet to rotate faster than a single ramp to ensure a longer bullet has completed its motion into a correct orientation for passage to be combined with a casing.

The improved fixed bullet orientation ramp 311 is shown in FIG. 3*a* and possesses the following dimensions in a preferred embodiment:

Base Front Width	312	25.04 mm;
Base Rear Width	313	14.39 mm;
Base Inside Length	314	38.75 mm;
Base Outside Length	315	63.75 mm;
Short Inside Ramp Height	321	13.10 mm;
Short Inside Ramp Length	322	22.50 mm;

-continued

Short Inside Ramp Width	323	2.00 mm;
Tall Outside Ramp Height	331	31.90 mm;
Tall Outside Ramp Length	332	36.15 mm;
Tall Outside Ramp Width	333	2.45 mm;
Tall Outside Ramp Angle	334	45°; and
Tall Outside Ramp Intersect	335	12.65 mm.

FIG. 3*c* illustrates a location of an improved fixed ramp 301 on a bullet loader 101 relative to the wheel 201. This location and function of fixed ramp 301 and rifle ramp 311 are identical to the location of a ramp described in the above patents to Koskela.

FIG. 4*a-f* illustrates various embodiments of a bullet orientation block utilizing varying sized spacers according to the present invention. During operation, wheel 201 rotates within a bullet hopper to capture and correctly orient a bullet for passage to a separate set of components that mate the bullet with a casing after it has been filled with a desired amount of propellant. The wheel 201 contains a series of openings around its circumference into which a bullet drops. These openings are size to accommodate a particular bullet

caliber size. As the wheel **201** rotates, the bullets that have fallen into these openings follow a path A such that each bullet passes over an orientation collator **406** and a series of grooves **407a-d**. These grooves are sized to catch a bullet in a point down orientation and assist in flipping it into a point up orientation. These grooves **407a-d** are also sized to permit an outer edge of a bullet already in a point up orientation to pass over without altering the bullet orientation.

These groove **407-d** are themselves oriented to direct a point of a bullet to move outward towards a horizontal position as the bullets moves along path A as wheel **201** rotates. When a point of a bullet reaches the end of a groove **407a-d**, the bullet point encounters a lower front edge of an improved fixed ramp **404** and continues to lift the point of the bullet as it moves up the ramp. By the time the point of a bullet has reached the raised end of the ramp **404**, the center of mass of the bullet has moved enough to cause the bullet to continue to a completely upward orientation within the opening of the wheel **201**.

In order for these grooves **407a-d** to properly engage the point of a bullet, an inner most point on the groove **407a-d** must be positioned to a location along the path A as the bullet moves. Depending upon the bullet caliber size, this inner most point may be different requiring configuration into a proper position each time a different bullet caliber size is to be processed by the bullet loader **101**. The grooves **407a-d** are located within orientation collator **406** that is part of a configuration block **402**. This configuration block **402** may be moved inward and outward from the center of the wheel **201** to adjust the location of the groove. An example of the movement of the configuration block **402** relative to wheel **201** is shown in detail in FIG. **4b**.

To make the configuration easier to set the inner most point at a proper location, a preferred embodiment of the present invention utilizes a predetermined sized space **422** to set the location of the innermost point of the groove **407a-d** to the desired location. The width of spacer **422** is determined by the bullet caliber size of the bullets being processed. Examples of different spacers having different widths are shown in detail in FIGS. **4c-e**.

Tables 1 and 2 above, recite known bullet caliber sizes and the configuration settings to be used to set up bullet loader **101**. As discussed above, this data identifies which of the fixed position ramps are to be used for a particular bullet caliber size. This data also identifies a particular spacer size, labeled 1-7 for pistol bullets and 5A for rifle bullets. In a preferred embodiment, each spacer is 54.40 mm long and 8.50 mm high. Table 3 provides thickness dimensions for each of the spacers identified above for the known bullet caliber sized.

TABLE 3

Spacer Size No.	Dimension (mm)	Bullet Type
1	3.05	Pistol
2	4.05	Pistol
3	4.60	Pistol
4	4.57	Pistol
5	5.50	Pistol
6	8.25	Pistol
7	9.60	Rifle
5A	6.25	Rifle

To configure the grooves, release knob **421** is loosened to permit configuration block **402** to move inward and outward from its base. In a preferred embodiment, release knob **421**

is 26.60 mm high with a 4 mm screw that is 33 mm in length. Other sizes may be used without deviating from the scope of the present invention as recited in the attached claims. The release knob is coupled to a bolt that screws against the base to hold the configuration block **402** in place. Once the knob **421** is loosened, the configuration block **402** moved outward to permit insertion of a properly sized spacer **422** depending upon the bullet caliber size to be processed. Any currently installed spacer may be removed and a new spacer having the needed width is installed. The configuration block **402** is pressed flush against the spacer **422** and the knob **421** is tightened to hold the configuration block **402** in its proper location. The use of these fixed spacers and configuration data from tables 1 and 2 make setting up the bullet loader **101** simpler and less prone to errors. FIG. **4f** illustrates an example embodiment of a configuration block **402** set to a desired location using a spacer according to the present invention.

FIG. **5a-b** illustrates various embodiments of a bullet path support according to the present invention. Once a bullet has been properly oriented as discussed above, the bullet falls through an opening to transverse a path from a hopper/orientation subsystem to a casing loading subsystem. This path between the two subsystems is typically defined by a hollow tube or spring that has an inner diameter comparable to the bullet caliber sizes. Typically the hopper/orientation subsystem is located above the casing loading subsystem permitting properly oriented bullets to fall via gravity.

The path of travel defined by the tube is generally in a downward direction through the tube which is typically flexible to permit operation in many locations and configurations. As such, restraining the flexible tube into an out of the way and convenient location while maintaining a significantly downward path is required. Any mechanism to restrain the position of the flexible tube must also maintain its inner diameter to permit the free passage of oriented bullets. FIG. **5a** illustrates an easily movable and configurable restraint **501** that allows the flexible tube to be restrained along a desired path.

The configurable restraint **501** consists of 3 parts: and an upper tube restraint **511**, a lower tube restraint **512**, and a mount **513**. The upper tube restraint **511** and lower tube restraint **512** may be coupled together at their edges to define an opening **521** through which the flexible tube may pass. The upper tube restraint **511** and lower tube restraint **512** are typically size to match an outer dimension of the flexible tube. These two pieces may be coupled together using any number of connection mechanism. Because the flexible tube is not expected to generate a significant force against these restraints, a preferred embodiment includes a coupling lip on one side of the upper tube restraint **511** and lower tube restraint **512** pair of components that snaps around protruding edge on the corresponding component. Many other coupling mechanisms known in the art may be used to place the restraints together around the flexible tube.

The lower tube restraint **512** also includes a mount connector **522** on one side that mates to a corresponding connection device **523** on mount **513**. In the preferred embodiment, the mount connector **522** is a ball that fits into a ball socket that acts as the corresponding connection device **523**. Such a connection mechanism provides an easy means to change the orientation of the upper tube restraint **511** and lower tube restraint **512** combination from the mount. A second side **524** of the mount **513** includes an attachment mechanism **525** for coupling the mount to a secure location to restrain the flexible tube. In the preferred embodiment, the attachment mechanism **525** is a slot to

13

surround a straight, rigid member found on or near the bullet loader **101**. Many other known devices may be used for attachment mechanism **525**. FIG. **5b** illustrates an example embodiment for use of the above restraint mechanism for the flexible tube disclosed herein.

FIG. **6a-b** illustrates various embodiments of a wheel removal handle according to the present invention. As noted above, different bullet caliber sizes use different rotating wheels **201** to provide openings sized appropriately to allow the rotation of the wheel **201** to properly orient the bullets for passage to the casing loading subsystem. Existing solutions lack a mechanism to easily permit the removal of one wheel **201** and replace it with a different sized wheel. Prior mechanism used to lift and inert wheels into the hopper/orientation subsystem were external devices to reach into and remove a wheel.

FIG. **6a** illustrates a wheel handle **601** that may be permanently attached to a wheel **201** while permitting operation of the wheel in the hopper/orientation subsystem. The wheel **201** possesses several thru holes that may be used along with a screw to attach a handle **601** to the wheel. When a handle **601** is attached towards the center of the wheel **201**, the handle **601** movement while the hopper/orientation subsystem is operating will keep the handle a sufficient distance away from the edge of the wheel **201**, and its openings that are used to orient a bullet. Addition of such a handle permanently upon a wheel **201** reduces the effort and time needed to switch wheels when different bullet caliber sizes are to be processed by the bullet loader **101**. FIG. **6b** illustrates an example wheel **201** that possess an attached handle **601** while the wheel is not installed within the hopper/orientation subsystem.

FIG. **7a-d** illustrates various embodiments of a bullet loader orientation jigs according to the present invention. Because the bullet loader **101** utilizes gravity to move the properly oriented bullets from the hopper/orientation subsystem, the hopper must be oriented in a desired position to ensure that bullets may easily fall from the wheel **201** into the flexible tube as discussed above. In different embodiments of the prior art bullet loaders, different mechanisms are used to support the hopper in position. FIG. **7a** illustrates one embodiment of orientation jig **701** used with a first embodiment of the bullet hopper **101**. Jig **701** is used to configure the hanging mechanism **721** utilizing two cylindrical supports shown in FIG. **7c-d**. FIG. **7b** illustrates a second embodiment of orientation jig **711** used with a first embodiment of the bullet hopper **101**. Jig **711** is used to configure the hanging mechanism utilizing straight support members **741** shown in FIG. **7e**.

The jigs **701**, **711** simply help position the bullet hopper on the hanger at the proper angle to allow the bullets to fall into the collator plate and then proceed around the hopper until they either fall into the nose guide and begin to rotate to flip upward or if they are already correctly oriented to continue to the drop point the only reason for the holes is it's part of the hanger assembly.

While the above embodiments of the present invention describe a bullet loader apparatus, one skilled in the art will recognize that the use various modifications to the ramp, spacers, and related components of a bullet loader may be used with the present invention as claimed. It is to be understood that other embodiments may be utilized, and operational changes may be made without departing from the scope of the present invention.

14

Unless explicitly stated otherwise, each numerical value and range should be interpreted as being approximate as if the word "about" or "approximately" preceded the value or range.

Unless otherwise indicated, all numbers expressing quantities of ingredients, properties such as molecular weight, percent, ratio, reaction conditions, and so forth used in the specification and claims are to be understood as being modified in all instances by the term "about," whether or not the term "about" is present. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the specification and claims are approximations that may vary depending upon the desired properties sought to be obtained by the present disclosure. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques. Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the disclosure are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard deviation found in the testing measurements.

It will be further understood that various changes in the details, materials, and arrangements of the parts which have been described and illustrated in order to explain embodiments of this invention may be made by those skilled in the art without departing from embodiments of the invention encompassed by the following claims.

In this specification including any claims, the term "each" may be used to refer to one or more specified characteristics of a plurality of previously recited elements or steps. When used with the open-ended term "comprising," the recitation of the term "each" does not exclude additional, unrecited elements or steps. Thus, it will be understood that an apparatus may have additional, unrecited elements and a method may have additional, unrecited steps, where the additional, unrecited elements or steps do not have the one or more specified characteristics.

What is claimed is:

1. A bullet-orienting apparatus for orienting bullets comprising a tip-end and a base-end, the apparatus comprising:
a bullet conveyance comprising a wheel having a perimeter defining one or more notches wherein each notch is sized to accommodate a bullet resting with either its tip-end or its base-end facing a nose plate when the notch is positioned above the nose plate; and
a bullet-orienting structure positioned adjacent the bullet conveyance such that a bullet conveyed from an upstream location to a downstream location by the bullet conveyance interacts with the bullet-orienting structure, wherein the bullet-orienting structure comprises:

the nose plate that extends at least partially below the wheel and being movable relative to the wheel, wherein the nose plate defines a tapered opening and a groove having a first end and a second end, wherein the first end of the groove is disposed adjacent to the tapered opening and wherein the tapered opening is positioned such that it is partially extends beneath the perimeter of the wheel and such that a bullet positioned in a notch of the wheel and oriented with its tip-end facing toward the tapered opening would fall into the tapered opening and such that a bullet positioned in a notch of the wheel and oriented with

15

its base-end facing toward the tapered opening would not fall into the tapered opening;
 a spacer adjacent to the nose plate below the wheel to orient the nose plate such that the groove is located in a position corresponding to a bullet caliber size to be processed; and
 a fixed location ramp having a first end and a second end, wherein the first end of the ramp is disposed adjacent to the second end of the groove, wherein the ramp is positioned downstream from the tapered opening, and wherein a bullet positioned in a notch with its base-end facing toward the tapered opening would interact with the ramp;
 wherein the fixed location ramp comprises a pistol bullet ramp and a rifle bullet ramp.

2. The bullet-orienting apparatus according to claim 1, wherein the bullet orienting structure further comprises a rotating knob having a thru screw to attach the nose plate into a desired location after the spacer has been installed.

3. The bullet-orienting apparatus according to claim 1, wherein the rifle bullet ramp comprises:

- a longer outside ramp having a first front edge and a rising slope to a first back edge; and
- a shorter inside ramp having a second front edge and a rising slope to a second back edge, the second back edge being adjacent to an intersection point along a front side of the longer outside ramp, and a front side of the shorter inside ramp oriented from the front side of the longer outside ramp at an angle of 45° measured between the first front edge and the second front edge.

4. The bullet-orienting apparatus according to claim 3, wherein the rifle bullet ramp further comprises solid base and ramp components having the following dimensions of approximately:

a base front width	25.04 mm;	
a base rear width	14.39 mm;	
a base inside length	38.75 mm;	
a base outside length	63.75 mm;	
a shorter inside ramp height	13.10 mm;	40
a shorter inside ramp length	22.50 mm;	
a shorter inside ramp width	2.00 mm;	
a longer outside ramp height	31.90 mm;	
a longer outside ramp length	36.15 mm;	
a longer outside ramp width	2.45 mm; and	
a longer outside ramp intersection point	12.65 mm.	45

5. The bullet-orienting apparatus according to claim 1, wherein the pistol bullet ramp comprises a solid ramp having the following dimensions of approximately:

an outside height	36.50 mm;	
an inside length	42.45 mm;	
an outside edge radius length	53.50 mm;	
an inside edge radius length	42.45 mm;	55
a front length	22.80 mm;	
a back length	26.00 mm;	
a lower edge length	23.04 mm; and	
a front ledge height	2.0 mm.	60

6. The bullet-orienting apparatus according to claim 1, wherein the spacer comprises a solid item having a width corresponding to the bullet caliber size being processed.

7. The bullet-orienting apparatus according to claim 1, wherein the wheel comprises a flat rotating disk and a handle coupled to a top side of the disk perpendicular to the top side of the disk.

16

8. The bullet-orienting apparatus according to claim 7, wherein the handle being permanently attached to the wheel using a bolt inserted into a thru hole in the disk.

9. The bullet-orienting apparatus according to claim 1, the pistol ramp and the rifle ramp are substituted for each other depending upon the bullet caliber size being processed.

10. Apparatus comprising:

- a bullet conveyance conveying bullets along a bullet conveyance path from an upstream location to a bullet-receiving opening at a downstream location, the bullets each including a tip end having a first width and a base end having a second width greater than the first width, the bullet conveyance taking up the bullets in tip down and tip up orientations whereby each of the bullets taken up by the bullet conveyance in the tip up orientation comprises a tip up bullet and each of the bullets taken up by the bullet conveyance in the tip down orientation comprises a tip down bullet; and

bullet-orienting structure interacting with each tip down bullet conveyed along the bullet conveyance path by the bullet conveyance between the upstream location and the downstream location rotating each tip down bullet relative to the bullet conveyance from the tip down orientation to the tip up orientation, the bullet-orienting structure comprising:

- a nose plate that extends at least partially below the wheel and being movable relative to the wheel, wherein the nose plate defines a tapered opening and a groove having a first end and a second end, wherein the first end of the groove is disposed adjacent to the tapered opening and wherein the tapered opening is positioned such that it is partially extends beneath the perimeter of the wheel and such that a bullet positioned in a notch of the wheel and oriented with its tip-end facing toward the tapered opening would fall into the tapered opening and such that a bullet positioned in a notch of the wheel and oriented with its base-end facing toward the tapered opening would not fall into the tapered opening;

- a spacer adjacent to the nose plate below the wheel to orient the nose plate such that the groove is located in a position corresponding to a bullet caliber size to be processed;

- a rotating knob having a thru screw to attach the nose plate into a desired location after the spacer has been installed; and

- a groove receiving the tip of each tip down bullet initially rotating each tip down bullet out of the tip down orientation toward the tip up orientation; and
- a fixed location ramp receiving the tip of each tip down bullet initially rotated from the groove rotating each tip down bullet into the tip up orientation;

wherein

- the fixed location ramp comprises a pistol bullet ramp and a rifle bullet ramp;

the rifle bullet ramp comprises:

- a longer outside ramp having a first front edge and a rising slope to a first back edge; and

- a shorter inside ramp having a second front edge and a rising slope to a second back edge, the second back edge being adjacent to an intersection point along a front side of the longer outside ramp, and a front side of the shorter inside ramp oriented from the front side of the longer outside ramp at an angle of 45° measured between the first front edge and the second front edge;

17

the pistol bullet ramp comprises a solid ramp having the following dimensions of approximately:

an outside height	36.50 mm;	5
an inside length	42.45 mm;	
an outside edge radius length	53.50 mm;	10
an inside edge radius length	42.45 mm;	
a front length	22.80 mm;	
a back length	26.00 mm;	
a lower edge length	23.04 mm; and	
a front ledge height	2.0 mm;	

the spacer comprises a solid item having a width corresponding to the bullet caliber size being processed; and the wheel comprises a flat rotating disk and a handle 15 coupled to a top side of the disk perpendicular to the top side of the disk.

* * * * *

18